

# EPDM joint tape

O225

Discover our innovative EPDM tape, a vulcanized, unreinforced water-resistant solution perfect for various modern sealing needs.

- Make facades water- and airtight
- Seamlessly seal windows and frames
- Achieve watertight perfection in gutters
- Effortlessly accomplish contact sealing

With contemporary technology, our EPDM tape provides reliable sealing for every application. Give your project the seal of the future.



**IPEX**

# Ipex EPDM

## EPDM joint tape 0225



WIDTH EPDM (MM)	LENGTH (M)
25 t/m 90	20/25
100 t/m 600	20/25
1.000 t/m 1.500	20/25

Standaard thickness 0,8mm  
other thicknesses on  
request.

Please note that customised  
boxes are only available on  
request.

GENERAL TECHNICAL DATA

ESSENTIAL CHARACTERISTICS	PERFORMANCE	TEST	TECHNICAL SPECIFICATIONS
Vapour control layer	EN 13984 type A		En 13984 : 2013
Reaction to fire	EN 13501-1	pass	
Watertightness (2kPa)	EN 1928		
Water vapour permeability	EN 1931	50000	
Impact resistance	EN 12691	NPD	
Joint shear resistance	EN 12316-2	NPD	
Tensile strength (both directions)	EN 12311-2	> 8 MPA	
Elongation (both directions)	EN 12311-2	> 300%	
Tear resistance	EN 12310-2	> 10 N	
Durability against ageing	EN 1296 / EN 1931		
Durability against alkali	Annex C	NPD	



Surface must be clean, dry, grease, dust, free from frost and free from loose materials. For cleaning of surfaces use IPA, surface must be dried before application.

### | TOEPASSING |



### | ALTERNATIVE |

EPDM SA  
with an acrylic adhesive layer



### | ALTERNATIVE |

EPDM SA  
with a butyl adhesive layer

